



UHP DV4 Diaphragm Valves

"Bulk Flow" Series



GTC Features

- Compact 1/2" Diaphragm Valve Design
- Serviceable, Modular Valves with Replaceable Seat Assembly
- C30 and C40 Pneumatic Actuators with Pop-Up Status Indicators
- Manual Actuator with Metal Handle, Positive Stop, and LOTO
- Replaceable Actuators without exposing wetted areas to atmosphere
- Multi-port Configurations available




Technical Data

Specification	K30	K30H (G2 only)	C30	C40	P30	H30
Actuation Type	Manual 1/2 Turn LOTO	Manual 1/2 Turn LOTO	Pneumatic N.C.	Pneumatic N.C.	Pneumatic N.O.	Hybrid 3/4 Turn Manual w/LOTO and Pneumatic N.C.
Actuation Port	n/a	n/a	1/8" OD Tube	1/8" OD Tube	10-32/M5	1/8" OD Tube
Actuation Pressure	n/a	n/a	70 to 120 psig	70 to 120 psig	70 to 120 psig	70 to 120 psig
Operating Pressure	Vac to 1500 psig*	Vac to 3000 psig	Vac to 1000 psig*	Vac to 1500 psig*	Vac to 500 psig	Vac to 1000 psig*
Expected Cycle Life	30K					
Flow Coefficient Cv	1.0					
Differential Back Pressure*	500 psid Max (note: this applies only to G1 version. G2 version is bi-directional)					
Proof / Burst Pressure	3,000 psig / 6,000 psig (4,500 psig / 9,000 psig for G2)					
Internal Volume	5.4 cc					
Operating Temperature	-20° to 160° F (Vespel seat option: -20° to 300° F)					
Helium Leak Rate	1 x 10 ⁻⁹ scc/s He					
Wetted Surface Roughness	10 Ra Max					
Wetted Surface Chemistry	Cr/Fe ≥ 1.5, CrO/FeO ≥ 2.0					
Wetted Surface Body Mat'l	316L VAR Stainless Steel					
Wetted Surface Other Mat'l	Diaphragm: Elgiloy™, Seat: PCTFE (optional Vespel™)					

Dimensions

Specification	K30/K30H	C30	C40	P30	H30
Overall Height (H)	3.5" [89 mm]	5.6" [142 mm]	6.5" [165 mm]	5.1" [129 mm]	6.9" [176 mm]
Actuator Diameter (D)	1.75" [44 mm]	1.69" [43 mm]	2.50" [64 mm]	1.69" [43 mm]	2.5" [64 mm]
Tube Stub Length (L)	0.880" [22.3 mm]				
1/2" Female Face Seal Length (L)	1.49" [38 mm]				
1/2" Male Face Seal Length (L)	2.16" [55 mm]				
3/4" Face Seal (L)	2.40" [61 mm]				



Ordering Information: C30-DV4-2A-TXTX-VS


Actuator

C30 - Pneumatic, N.C., 1000 psig
C40 - Pneumatic, N.C., 1500 psig
K30 - Manual, 1/2 Turn, LOTO, 1500 psig
K30H - Manual, 1/2 Turn, LOTO, 3000 psig
P30 - Pneumatic, Normally Open, 500 psig
H30 - Hybrid, 3/4 Turn, LOTO, N.C., 1000 psig


Body Series

DV4 - Bulk Series

Porting



-- Internal Top View --



1 2 3 4
Ports

Options

VS - Vespel™ Seat
BK - Black Handle Color
GR - Green Handle Color
RD - Red Handle Color
WH - White Handle Color
YW - Yellow Handle Color

Connections

X - (No port)
T - 1/2" Tube Stub
M - 1/2" Male Face Seal
F - 1/2" Female Face Seal
M12 - 3/4" Male Face Seal
F12 - 3/4" Female Face Seal